

SKN 7500



Caseless Disc Diode

Rectifier Diode

SKN 7500

Preliminary data

Features

- High current diode in a slim package without external case
- Metal pressure contacts for double or single side cooling
- Reverse voltages up to 600 V
- Low power dissipation and low thermal resistance
- Available in matched groups for paralleling

Typical Applications

- High current rectifiers
- Welding
- Electroplating


1) DSC = Double Side Cooling
SSC = Single Side Cooling

V_{RSM} V	V_{RRM} V	$I_{FRMS} = 11800$ A (maximum value for cont. operation) $I_{FAV} = 7500$ A (sin. 180; $T_c = 85$ °C)
600	600	SKN 7500/06

Symbol	Condition	Values	Units
I_{FAV}	sin. 180 ; $T_c = 85$ °C	7500	A
	sin. 180 ; $T_c = 100$ °C	6700	A
I_{FSM}	$T_{vj} = 25$ °C ; 10 ms	60	kA
	$T_{vj} = 180$ °C ; 10 ms	50	kA
i^2t	$T_{vj} = 25$ °C ; 8,3...10 ms	18000	kA ² s
	$T_{vj} = 180$ °C ; 8,3...10 ms	12500	kA ² s
V_F	$T_{vj} = 25$ °C, $I_F = 8000$ A	Max. 1,12	V
$V_{(TO)}$	$T_{vj} = 180$ °C	Max 0,7	V
r_T	$T_{vj} = 180$ °C	Max 0,038	mΩ
I_{RD}	$T_{vj} = 25$ °C ; $V_R = V_{RRM}$	Max. 4	mA
	$T_{vj} = 180$ °C ; $V_R = V_{RRM}$	Max. 100	mA
$R_{th(j-c)}$	DSC ¹⁾	9,0	K/kW
	SSC anode / SSC cathode ¹⁾	12,4 / 33	K/kW
$R_{th(c-s)}$	DSC / SSC ¹⁾	5 / 10	K/kW
T_{vj}		-40...+180	°C
T_{stg}		-40...+180	°C
V_{isol}		-	V~
F	mounting force (SI units)	24 ... 30	kN
	mounting force (US units)	5400...6750	lbs.
a		5 * 9,81	m/s ²
m	approx.	78	g
Case	Ø49,5 x 5 mm	E28	



SKN



Case: E28

***IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged noninfringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.